

SilverCATH[®] 210

PRECISION AUTOFEED, AUTOCUT, TIP FORMING MACHINES

Quality tips from start to finish. Silverstone's catheter-introducer tip forming machines create your quality product with induction heating and precision controls integrated into a robust design. The model 210 includes automatic tube feeder and precision cutting.



BACKED BY TWO DECADES OF TIP FORMING EXPERIENCE

SilverCATH[®] machines deliver performance and flexibility. The recipe driven process allows the customer to fine tune their tip forming process for their unique product design.

SilverCATH[®] utilizes industrial level hardware. Closed loop induction power supplies and servo driven motions are under coordinated PLC control.

The SilverCATH[®] systems are turn-key machines. SilverCATH machines conserve your valuable floor space and the vertical process geometry simplifies product loading.

SilverCATH[®] is compatible with a wide range of catheter-introducer lengths and diameters. Let Silverstone configure a machine for your application.

SilverCATH® 210

PRECISION AUTOFEED, AUTOCUT, TIP FORMING MACHINES

SC110EN20.03

- Solid-state induction power supply with closed-loop power feedback
- Robust fixed geometry heating head that ensures consistent product tips time after time
- 10" color touch screen for quick parameter setting and selection
- Adjustable pre-forming and forming heat settings
- Process parameters that can be changed, saved, and recalled
- Adjustable forming force
- Servo-driven motion for precision and speed
- Ball slides for smooth and controlled motions
- Compact footprint to save valuable floor space
- Versatile tooling platform that can be configured to handle a wide range of tube lengths and gauges
- Category 3 safety and NFPA 79 implementation
- Built for production work, yet flexible enough for research and development



Specification	SilverCATH® 210
Catheter/Introducer Processing	1-up
Induction Power Supply	1kW, solid-state, air cooled
Power Output Regulation	Closed loop
Operator Interface	10" color touch screen
Saved Process Recipes	Yes
Forming Motions	Servo motor with absolute encoder
Coil	Air cooled, fixed geometry
Die Block Cooling	Air or recirculating water
Forming Force	Adjustable
Raw tube length	12 to 36"
Tube cut lengths	4 to 12"
Air Supply Requirements	80 psi
Power Input	208-240 VAC, 50/60 Hz
Footprint (w x d)	57" x 35"
Intended Applications	Production and R&D